

# RBG 1000 G



The RBG 1000 G has a higher gear ratio. This means that at very low feed rates ( $< 10$  mm/h), the feed rate can be better adjusted by means of a potentiometer.

The maximum feed rate is 300 mm/h.

## OPERATION PRINCIPLE

## BENEFITS

- Feed rates < 10 mm/h can be set precisely with the aid of a potentiometer
- Optional: pressure-resistant up to 3 bar, remote control or computer-controlled
- Highest short-term and long-term dosing constancy
- Disperses virtually all non-cohesive dusts
- Easy exchange of different solid material reservoirs and dispersing covers
- Easy determination and adjustment of the mass flow
- Pulse mode
- Device easy to clean
- Quick and easy to operate
- Reliable operation
- Little maintenance required
- Reduces your operating expenses

## DATASHEET

Particle size range	0.1 – 100 $\mu\text{m}$
Maximum particle number concentration	Ca. $10^7$ particles/ $\text{cm}^3$
Volume flow	0.5 – 5.0 $\text{m}^3/\text{h}$
Mass flow (particles)	0.04 – 185 g/h (with an assumed compacted density of 1 g/ $\text{cm}^3$ )
Filling height	70 mm
Filling quantity	2.7 g (reservoir $\varnothing$ = 7 mm), 5.5 g (reservoir $\varnothing$ = 10 mm), 10.8 g (reservoir $\varnothing$ = 14 mm), 22 g (reservoir $\varnothing$ = 20 mm), 43 g (reservoir $\varnothing$ = 28 mm)
Power supply	115 – 230 V, 50/60 Hz
Particle material	Non-cohesive powders and bulks
Dosing time	Several hours nonstop
Pre-pressure	4 – 8 bar
Carrier/dispersion gas	Random (generally air)
Maximum counter pressure	0.2 barg
Compressed air connection	Quick coupling
Feed rate	1 – 300 mm/h
Reservoir inner diameter	7, 10, 14, 20, 28 mm
Aerosol outlet connection	Dispersion cover type A: $\varnothing_{\text{inside}}$ = 5 mm, $\varnothing_{\text{outside}}$ = 8 mm Dispersion cover type B: $\varnothing_{\text{inside}}$ = 3.6 mm, $\varnothing_{\text{outside}}$ = 6 mm Dispersion cover type C: $\varnothing_{\text{inside}}$ = 2.5 mm, $\varnothing_{\text{outside}}$ = 6 mm
Dispersion cover	Type A, type B, type C, type D
Dimensions	465 • 320 • 200 mm (H • W • D)
Weight	Approx. 19 kg

## APPLICATIONS

- Applications with very low feed rates (<10 mm/h)
- Filter industry:
  - Determination of fractional separation efficiency
  - Determination of total separation efficiency
  - Long-term dusting
  - Filter media and ready-made filters
  - Dust removal filters
  - Vacuum cleaners and vacuum cleaner filters
  - Car interior filters
  - Engine air filters
- Calibration of particle measurement devices
- Flow visualization
- Inhalation tests
- Tracer particles for LDA, PIV, etc.
- Coating of surfaces



Mehr Informationen:  
<https://www.palas.de/product/rbg1000g>