

# AQ GUARD SMART 1000



AQ Guard Smart 1000 is a compact and cloud-enabled air quality measurement device. The system is designed for the requirements of outdoor air measurement in the smart city environment to improve granularity while maintaining high comparability to official measurements for environmental monitoring and health protection.

## BENEFITS

- Quick and easy installation
- Long-term stability (24/7) and low maintenance
- Flexibility in communication and data transmission
- Reliable measurements (near-reference standard for particles)
- Simultaneous measurement of PM<sub>1</sub>, PM<sub>2.5</sub>, PM<sub>4</sub>, PM<sub>10</sub>, TSP, C<sub>N</sub>
- Versatile application possibilities even in demanding environments
- Suitable for high dust concentrations
- Access to data in real time and with high temporal resolution

## APPLICATIONS

- Urban air quality monitoring
- Smart city projects
- Open pit mining and landfills
- Formation and dispersion studies
- Construction sites
- Immission monitoring of industrial plants
- Measurement of dust emissions from road and rail traffic as well as ports
- Risk areas (natural and anthropogenic)

## FEATURES

- On-site calibration and adjustment (particle size and volume flow)
- Communication via GPRS / 3G / 4G / Ethernet / Wi-Fi, optional: LoRaWAN
- Technology based on the certified Fidas® 200 series
- Expandable with third-party devices, metrology and sensors
- Data visualization via Palas Cloud (MyAtmosphere-ready)
- Secondary measurement data acquisition

## DATASHEET

Measuring principle	Optical light scattering at single particles	Reported data	PM <sub>1</sub> , PM <sub>2.5</sub> , PM <sub>4</sub> , PM <sub>10</sub> , TSP, CN, CO <sub>2</sub> , particle size distribution, pressure, temperature, relative humidity
Measurement (number C <sub>N</sub> )	range 0 – 20,000 particles/cm <sup>3</sup>	Measurement (size)	range 0.175 – 20 µm
Measurement (mass)	range 0 – 100 mg/m <sup>3</sup> (depending on the composition of the aerosol)	Size channels	64 (32/decade)
Time resolution	1 min, moving average 1 min (MyAtmosphere), every second via internal protocols	Interfaces	USB, Ethernet (LAN), Wi-Fi, 3G/4G via Modem, optional: LoRaWAN
Protocols	ASCII, MODBUS, UDP	Light source	Long term stable LED
Power supply	Supplied power supply: 12 V	Power consumption	Standard operation: 1.2 A (1.7 A with additional heating)
Installation conditions	-20 – +50 °C	Dimensions	530 • 270 • 208 mm (H • W • D)
Weight	Approx. 6 kg	Special features	Heated inlet, mast / tripod mount
Data Management	Prepared for connection to the Palas Cloud MyAtmosphere ("MyAtmosphere-ready"); Internet access and separate registration required. The MyAtmosphere terms of use apply.		