

AQ GUARD SMART 1000



AQ Guard Smart 1000 is a compact and cloud-enabled air quality measurement device. The system is designed for the requirements of outdoor air measurement in the smart city environment to improve granularity while maintaining high comparability to official measurements for environmental monitoring and health protection.

BENEFITS

- Technology based on the certified Fidas® 200 series (EN 16450 and MCERTS)
- Simultaneous measurement of PM₁, PM_{2.5}, PM₄, PM₁₀, C_N with high temporal resolution
- Easy and fast installation
- Data visualization via cloud MyAtmosphere
- Communication via GPRS / 3G / 4G / Ethernet / Wi-Fi, optional: LoRaWAN
- Extendable with weather station / solar protection

APPLICATIONS

- Urban air quality monitoring
- Smart city projects
- Open pit mining and landfills
- Formation and dispersion studies
- Construction sites
- Immission monitoring of industrial plants
- Measurement of dust emissions from road and rail traffic as well as ports
- Risk areas (natural and anthropogenic)

DATASHEET

Measurement range (number C_N)	0 – 20,000 particles/cm ³
Size channels	64 (32/decade)
Measurement range (size)	0.175 – 20 μm
Measuring principle	Optical light scattering at single particles
Reported data	PM ₁ , PM _{2.5} , PM ₄ , PM ₁₀ , TSP, CN, particle size distribution, ambient pressure, ambient temperature, rel. ambient humidity, optional: SO ₂ , CO, NO ₂ , O ₃
Measurement range (mass)	0 – 100 mg/m ³ (depending on the composition of the aerosol)
Time resolution	1 min, moving average 1 min
Light source	Long term stable LED
Power consumption	Standard operation: 1.2 A (1.7 A with additional heating)
Weight	Approx. 6 kg
Installation conditions	-20 – +50 °C
Interfaces	USB, Ethernet (LAN), Wi-Fi, 3G/4G via Modem, optional: LoRaWAN
Protocols	ASCII, MODBUS, UDP
Power supply	Supplied power supply: 12 V
Special features	Heated inlet, mast / tripod mount



Further information:
<https://www.palas.de/product/aq-guard-smart1000>