

# AQ GUARD



AQ Guard, currently the most advanced compact analyzer for determining indoor air quality, continuously and reliably analyses airborne fine dust particles in the range 0.175 – 20  $\mu\text{m}$  (\*1 IAHP-Package starting from 0.15  $\mu\text{m}$ ). A newly developed mass conversion algorithm calculates PM values based on single particle optical light scattering, considering signal duration and shape.

AQ Guard simultaneously calculates and stores PM<sub>1</sub>, PM<sub>2.5</sub>, PM<sub>4</sub>, and PM<sub>10</sub>, the total dust load, the particle number concentration CN, and the particle size distribution. Thus, AQ Guard provides comprehensive, accurate information on indoor particulate matter. This is only possible in this form with a counting single particle measurement method.

## BENEFITS

- Technology based on the type approved Fidas® 200 series (EN16450 and MCERTS); simultaneous measurement of CN, PM<sub>1</sub>, PM<sub>2.5</sub>, PM<sub>4</sub>, PM<sub>10</sub>
- With the "Indoor Air Hygiene Professional" extension: increased counting efficiency for nano-scaled particles from 0.15  $\mu\text{m}$
- Computation of air quality index based on measurements of particulates, CO<sub>2</sub>
- Estimation of infection risk based on measurements of CO<sub>2</sub> and particulate matter
- High accuracy due to advanced algorithms
- Long term stable due to self-calibration for measurement of flow rate, particulates, and gaseous pollutants
- Operates on AC, DC, or power-over-Ethernet

## APPLICATIONS

- Industry: production processes, bulk material handling (mixing, discharge, storage, packaging, etc.), fenceline monitoring
- Construction sites: roads, railroads, demolition sites
- Buildings: schools, kindergartens, hospitals, hotels, offices, public service buildings,
- Residential buildings near construction sites or other polluted areas
- Public transportation: airports, train stations, tramway & underground stations, cruise ships, passenger cabins, e.g., in trams, train

## FEATURES

- On-site calibration and adjustment (particle size and volume flow)
- 7" touch display
- Data visualization via Palas Cloud ("MyAtmosphere-ready")
- Measurement data acquisition per second
- Workplace measurements via AQControl: connection of up to six AQ Guard systems and one PAG 1000 aerosol generator possible

## DATASHEET

Measuring principle	Optical light scattering at single particles
Reported data	PM <sub>1</sub> , PM <sub>2.5</sub> , PM <sub>4</sub> , PM <sub>10</sub> , TSP, CN, particle size distribution, ambient pressure, ambient temperature, rel. ambient humidity, CO <sub>2</sub> , Infection Risk Index, Air Quality Index (depending on configuration)
Measurement range (number C <sub>N</sub> )	0 – 20,000 particles/cm <sup>3</sup>
Measurement range (size)	0.178–20 μm (with IAHP extension from 0.150 μm)
Measurement range (mass)	0 – 20,000 μg/m <sup>3</sup>
Measurement uncertainty	R <sub>2</sub> > 0.98 for PM <sub>2.5</sub> and R <sub>2</sub> > 0.94 for PM <sub>10</sub> versus EN 16450-certified Fidas <sup>®</sup> 200 (15 min average, each)
Volume flow	1 l/min $\hat{=}$ 0.06 m <sup>3</sup> /h
Size channels	64 (32/decade)
Interfaces	USB, Ethernet (LAN), Wi-Fi, 4G (optional via LTE stick)
User interface	Touchscreen, 800 • 480 pixel, 5" (12.7 cm)
Protocols	UDP, ASCII
Data logger storage	10 GB
Software	PDAnalyze
Data acquisition	Digital, 22 MHz processor, 256 raw data channels
Light source	Long term stable LED
Operating system	Windows 10 IoT Enterprise
Power consumption	< 20 W
Installation conditions	-20 – +50 °C
Response time	1 s, moving average configurable
Aerosol conditioning	Optional: thermal with compact IADS
Dimensions	175 • 280 • 140 mm (H • W • D)
Weight	2.4 kg
Linearity	0.95 – 1.05 (measured against EN 16450 certified Fidas <sup>®</sup> 200)

## NORMS AND CERTIFICATES

ISO 21501-1