BEG 2000 C







This dispersion system is able to generate high mass flows continuously, e.g., 7.3 kg/h, with optimal dosing constancy and control with automatic mass flow monitoring. Mass flow setting of approx. 350 g/h - 7.3 kg/h based on SAE fine, A2 dust.

BENEFITS

- Excellent short-term and long-term dosing constancy
- Easy to operate
- · Quick and easy to clean
- Remote control or computer-controlled
- Pulse mode
- Easy to fill while in operation
- Large reservoir (1,500 cm³)
- Automatic mass flow control with the BEG 2000
- Robust design, proven in industrial applications

APPLICATIONS

- · Loading test of
 - Engine filters as per ISO 5011
 - Hot gas filters
 - Bag filters
 - Air filters
 - Cyclones
- Engine crash test
- Chemical and pharmaceutical industry
- · Cement industry



DATASHEET

Particle size range	0.1 – 200 μ m	Maximum particle number concentration	Ca. 10 ⁷ particles/cm ³
Volume flow	80–165 NI/min	Mass flow (particles)	Type C: 350 – 7,300 g/h (with reference to SAE Fine, A2 dust)
Filling quantity	500 g	Power supply	115 – 230 V, 50/60 Hz
Particle material	Non-cohesive powders and bulks	Dosing time	Several hours nonstop
Pre-pressure	4 – 8 bar	Carrier/dispersion gas	Random (generally air)
Compressed air connection	Quick coupling	Aerosol outlet connection	Type A: $\emptyset_{inside} = 6.4$ mm, $\emptyset_{outside} = 10$ mm Type B: $\emptyset_{inside} = 8$ mm, $\emptyset_{outside} = 12$ mm Type C: $\emptyset_{inside} = 6.2$ mm, $\emptyset_{outside} = 10$ mm
Reservoir volume	1,500 cm ³		