

PROMO[®] 1000 P



Depending on the aerosol composition to be measured, i.e., the carrier gas component and the particle material, pressure changes in the carrier gas can significantly influence the particle size distribution, e.g., due to condensation or evaporation.

For this reason, the **aerosol sensor welas[®] 1100 P¹** and the **aerosol sensor welas[®] 1200 P²** are equipped with a pressure-tight cuvette to ensure isobaric and isothermal sampling into the sensor's measurement volume.

The Promo[®] system is usually calibrated for the operating volume flow. As the operating volume flow changes with pressure, it is advantageous for the user if automatic volume flow regulation for the sampling volume flow is provided for in the device.

In the Promo[®] 1000 P, the pressure of the carrier gas is measured, and the required operating volume flow is automatically set to 5 l/min.

Includes:

- Mass flow controller ...

¹ aerosol sensor welas[®] 1100 P: <https://www.palas.de//product/aerosolsensorwelas1100P>

² aerosol sensor welas[®] 1200 P: <https://www.palas.de//product/aerosolsensorwelas1200p>

BENEFITS

Measuring range of 200 nm to 40 μm (3 measuring ranges selectable in one device)

Up to three measuring ranges in only one device:

- 0.2 μm – 10 μm
- 0.3 μm – 17 μm
- 0.6 μm – 40 μm

Up to 128 size channels per measuring range

Concentration range from $< 1 \text{ particle/cm}^3$ to $5 \cdot 10^5 \text{ particles/cm}^3$

Calibration curves for different refractive indices

Very high and reproducible counting efficiency rate starting at 0.2 μm

High temporal resolution down to 10 ms

PDAnalyze analysis software

Calibration, cleaning and lamp replacement can all be performed independently by the customer

External control by RS 232 or Ethernet

Optional: Software PDControl for operation as welas® digital available

Simple operation

Low maintenance

Reliable function

Reduces your operating expenses

APPLICATIONS

- Up to three measuring ranges can be selected in one device: 0.2 μm – 10 μm | 0.3 μm – 17 μm | 0.6 μm – 40 μm

FEATURES

- Up to four measuring ranges can be selected in one device: 0.12 μm - 3.5 μm | 0.2 μm - 10 μm | 0.3 μm - 17 μm | 0.6 μm - 40 μm

DATASHEET

Measuring principle	Optical light-scattering	Measurement range (number C_N)	$< 5 \cdot 10^5$ particles/cm ³
Measurement range (size)	0.2 – 10 μm , 0.3 – 17 μm , 0.6 – 40 μm	Volume flow	5 l/min, 1.6 l/min
Size channels	Max. 128 (64/decade)	Time resolution	1 s
Interfaces	USB, Ethernet (LAN), Wi-Fi, RS-232/485	User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Data logger storage	4 GB Compact Flash	Software	PDControl, FTControl, PDAnalyze
Thermodynamic conditions	+10 – +40 °C, -100 – 50 mbar	Data acquisition	Digital, 20 MHz processor, 256 raw data channels
Light source	Xenon high pressure lamp 75 W	Housing	Table housing, optional: with mounting brackets for rack-mounting
Support options	Direct remote access, Palas webserver service	Operating system	Windows embedded
Power supply	115 – 230 V, 50/60 Hz	Power consumption	100 W
Installation conditions	+5 – +40 °C (control unit)	Dimensions	185 • 450 • 315 mm (H • W • D) (19")

additional parameter on our website ...