

PROMO[®] 2000



Promo[®] 2000 is a light-scattering aerosol spectrometer system for particle size analysis and concentration determination that can be equipped with all welas[®] sensors. On Promo[®] 2000, the welas[®] sensors equipped with different measurement volumes, as required, can be easily connected via fiber optic cables and interchanged as needed. These sensors allow reliable measurement in the concentration range from < 1 particle/cm³ to 10⁶ particles/cm³ in gases.

Promo[®] 2000 is famous for up to 128 size channels per measuring range and a concentration range from < 1 particle/cm³ to 10⁶ particles/cm³.

BENEFITS

- Very high size resolution
- Concentration range from < 1 particle/cm³ to 10⁶ particles/cm³
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency even from 0.2 μm
- Pressure resistant up to 10 bar (optional)
- Heatable up to 250°C (optional)
- Optical fiber technology
- Easy to operate thanks to large touch display
- Calibration, cleaning, and lamp replacement can be carried out independently by the customer
- External control via RS 232 or Ethernet

FEATURES

- Up to four measuring ranges: 0.2 μm - 10 μm | 0.3 μm - 17 μm | 0.6 μm - 40 μm | 2 μm - 100 μm
- Up to 128 size channels per measuring range
- Clear calibration curve thanks to white light source with 90° stray light detection
- Patented T-aperture: No edge zone error
- Digital single signal processing: Coincidence detection and correction on the single signal
- Selectable sensors for optimized measurement with regard to concentration
- On-site calibration and adjustment (particle size and volume flow)

<https://www.palas.de/en/product/promo2000>

APPLICATIONS

- Emission monitoring of installations
- Control of grinding and classification processes
- Monitoring of production processes in the food, pharmaceuticals and chemicals industries
- Testing of complete filters, inertial and wet separators or electrostatic precipitators

MODEL VARIATIONS



Promo[®] 2000 H

With heating control up to 250 °C for welas[®] aerosol sensors

<https://www.palas.de/en/product/promo2000h>



Promo[®] 2000 HP

Version with automatic regulation of the sampling flow through the welas[®] aerosol sensors at an overpressure of 2 to 10 bar or with heating regulation to 120 °C

<https://www.palas.de/en/product/promo2000hp>

DATASHEET

Measuring principle	Optical light-scattering
Measurement range (number C_N)	$< 1 \cdot 10^6$ particles/cm ³
Measurement range (size)	0.2 – 10 μm , 0.3 – 17 μm , 0.6 – 40 μm , 2 – 100 μm
Volume flow	5 l/min
Size channels	Max. 128 (64/decade)
Interfaces	USB, Ethernet (LAN), Wi-Fi, RS-232/485
User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Data logger storage	4 GB Compact Flash
Software	PDControl, FTControl, PDAnalyze
Data acquisition	Digital, 20 MHz processor, 256 raw data channels
Light source	Xenon arc lamp 35 W
Housing	Table housing, optional: with mounting brackets for rack-mounting
Support options	Direct remote access, Palas webserver service
Operating system	Windows embedded
Power consumption	100 W
Installation conditions	+5 – +40 °C (control unit)
Dimensions	185 • 450 • 315 mm (H • W • D) (19")
Weight	Control unit: approx. 8 kg, sensor: approx. 2.8 kg