



The *welas*[®] aerosol sensors *welas*[®] 2070 HP, 2100 HP, 2300 HP and *welas*[®] 2500 HP are equipped with a cuvette heatable up to 120 °C and pressure-tight up to 10 barg to ensure isobaric and isothermal sampling into the sensor's measurement volume. The *Promo*[®] system is usually calibrated for the operating volume flow. As the operating volume flow changes with pressure and temperature, it is advantageous for the user if automatic volume flow regulation for the sampling volume flow is provided for in the device.

In the *Promo*[®] 2000 HP the pressure and temperature of the carrier gas are measured and the required operating volume flow is automatically set to 5 l/min.

OPERATION PRINCIPLE

Includes:

- Mass flow controller for volume flow regulation
- Heating regulator up to 120 °C
- Temperature sensor
- Absolute pressure capsule
- Filter unit to protect the flow rate control

BENEFITS

- Very high size resolution
- Concentration range from < 1 particle/cm³ to 10^6 particles/cm³
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency even from $0.2 \mu\text{m}$
- Pressure resistant up to 10 bar (optional)
- Heatable up to 250°C (optional)
- Optical fiber technology
- Easy to operate thanks to large touch display
- Calibration, cleaning, and lamp replacement can be carried out independently by the customer
- External control via RS 232 or Ethernet

DATASHEET

Measuring principle	Optical light-scattering
Measurement range (number C_N)	$< 1 \cdot 10^6$ particles/cm ³
Measurement range (size)	0.2 – 10 μ m, 0.3 – 17 μ m, 0.6 – 40 μ m, 2 – 100 μ m
Volume flow	5 l/min
Size channels	Max. 128 (64/decade)
Interfaces	USB, Ethernet (LAN), Wi-Fi, RS-232/485
User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Data logger storage	4 GB Compact Flash
Software	PDControl, FTControl, PDAnalyze
Data acquisition	Digital, 20 MHz processor, 256 raw data channels
Light source	Xenon arc lamp 35 W
Housing	Table housing, optional: with mounting brackets for rack-mounting
Support options	Direct remote access, Palas webserver service
Operating system	Windows embedded
Power consumption	100 W
Installation conditions	+5 – +40 °C (control unit)
Dimensions	185 • 450 • 315 mm (H • W • D) (19")
Weight	Control unit: approx. 8 kg, sensor: approx. 2.8 kg

APPLICATIONS

- Emission monitoring of installations
- Control of grinding and classification processes
- Monitoring of production processes in the food, pharmaceuticals and chemicals industries
- Testing of complete filters, inertial and wet separators or electrostatic precipitators



Mehr Informationen:
<https://www.palas.de/en/product/promo2000hp>