



The Promo[®] 3000 is a light-scattering aerosol spectrometer system with two sensors for particle size analysis and concentration determination that can be equipped with all welas[®] sensors. On Promo[®] 3000, the welas[®] sensors equipped with different measurement volumes, as required, can be easily connected via fiber optic cables and interchanged as needed. These sensors allow reliable measurement in the concentration range from < 1 particle/cm³ up to 10⁶ particles/cm³ and are available for measurement in gases and liquids.

Promo[®] 3000 is famous for up to 128 size channels per measuring range and a concentration range from < 1 particle/cm³ to 10⁶ particles/cm³.

BENEFITS

- Very high size resolution
- Concentration range from < 1 particle/cm³ to 10⁶ particles/cm³
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency starting at 0.2 μm
- Optical fiber technology
- Easy operation thanks to large touch display
- Calibration, cleaning, and lamp replacement can be performed independently by the customer
- External control via RS 232 or Ethernet
- Low maintenance

FEATURES

- Two sensors can be connected for raw and clean gas measurement
- Up to four measuring ranges: 0.2 μm - 10 μm | 0.3 μm - 17 μm | 0.6 μm - 40 μm | 2 μm - 100 μm
- Up to 128 size channels per measuring range
- Clear calibration curve thanks to white light source with 90° scattered light detection
- Patented T-aperture: No edge zone error, coincidence detection and correction on the individual signal
- Selectable sensors for optimized measurement with regard to concentration
- On-site calibration and adjustment (particle size and volume flow)

APPLICATIONS

- Emission monitoring of installations
- Control of grinding and classification processes
- Monitoring of production processes in the food, pharmaceuticals and chemicals industries
- Testing of complete filters, inertial and wet separators or electrostatic precipitators

MODEL VARIATIONS



Promo[®] 3000 H

With heating control up to 250 °C for welas[®] aerosol sensors

<https://www.palas.de/product/promo3000h>



Promo[®] 3000 HP

Version with automatic regulation of sampling volume flow by the aerosol sensors welas[®] under overpressure up to 10 bar or in temperatures to 120 °C

<https://www.palas.de/product/promo3000hp>

DATASHEET

Measuring principle	Optical light-scattering	Measurement range (number C_N)	$< 1 \cdot 10^6$ particles/cm ³
Measurement range (size)	0.2 – 10 μ m, 0.3 – 17 μ m, 0.6 – 40 μ m, 2 – 100 μ m	Volume flow	5 l/min
Size channels	Max. 128 (64/decade)	Time resolution	1 s
Interfaces	USB, Ethernet (LAN), Wi-Fi, RS-232/485	User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Data logger storage	4 GB Compact Flash	Software	PDControl, FTControl, PDAnalyze
Thermodynamic conditions	+10 – +40 °C, -100 – 50 mbar	Data acquisition	Digital, 20 MHz processor, 256 raw data channels
Light source	Xenon arc lamp 35 W	Gehäuse	Table housing, optional: with mounting brackets for rack-mounting
Support options	Direct remote access, Palas webserver service	Operating system	Windows embedded
Power supply	115 – 230 V, 50/60 Hz	Power consumption	100 W
Installation conditions	+5 – +40 °C (control unit)	Dimensions	185 • 450 • 315 mm (H • W • D) (19")

additional parameter on our website ...