

RBG 1000 GD



The RBG 1000 G has a higher gear ratio. This means that at very low feed rates (< 10 mm/h) the feed rate can be better adjusted by means of a potentiometer.

Optional operation with low pressure from 300 mbar absolute is possible.

The feedstock reservoirs with a diameter of 7, 10, 14, or 20 mm are pressure-resistant.

For operation with low pressure, special pressure-resistant feedstock reservoirs are needed. Their piston is strongly connected to the feeding unit by a claw. This enables an undisturbed operation with low pressure. Old RBG models can be upgraded with this function by Palas®.

The feedstock reservoir with a diameter of 28 mm is not pressure-resistant but can be used with the RBG 1000 ID under atmospheric conditions.

In the RBG 1000 D pressure-resistant version, compressed air is used as the disgerger gas. Operation with nitrogen or other inert gases is not permitted.

BENEFITS

- Pressure-resistant up to 3 barg overpressure
- Very low feed rates (< 10 mm/h) can be set precisely with the aid of a potentiometer
- Optional: Remote control or computer-controlled

APPLICATIONS

- All applications pressure-resistant up to 3 barg overpressure
- Applications with very low feed rates (< 10 mm/h)
- Testing of compressed air filters

DATASHEET

Particle size range	0.1 – 100 μm	Maximum particle number concentration	Ca. 10^7 particles/ cm^3
Volume flow	0.5 – 5.0 m^3/h	Mass flow (particles)	0.04 – 185 g/h (with an assumed compacted density of 1 g/ cm^3)
Filling height	70 mm	Filling quantity	2.7 g (reservoir \varnothing = 7 mm), 5.5 g (reservoir \varnothing = 10 mm), 10.8 g (reservoir \varnothing = 14 mm), 22 g (reservoir \varnothing = 20 mm), 43 g (reservoir \varnothing = 28 mm)
Power supply	115 – 230 V, 50/60 Hz	Particle material	Non-cohesive powders and bulks
Dosing time	Several hours nonstop	Pre-pressure	4 – 8 bar
Carrier/dispersion gas	Random (generally air)	Maximum counter pressure	0.2 barg
Compressed air connection	Quick coupling	Feed rate	1 – 300 mm/h
Reservoir inner diameter	7, 10, 14, 20, 28 mm	Aerosol outlet connection	Dispersion cover type A: $\varnothing_{\text{inside}}$ = 5 mm, $\varnothing_{\text{outside}}$ = 8 mm Dispersion cover type B: $\varnothing_{\text{inside}}$ = 3.6 mm, $\varnothing_{\text{outside}}$ = 6 mm Dispersion cover type: $\varnothing_{\text{inside}}$ = 2.5 mm, $\varnothing_{\text{outside}}$ = 6 mm
Dispersion cover	Type A, type B, type C, type D	Dimensions	465 • 320 • 200 mm (H • W • D)
Weight	Approx. 19 kg		