


# RBG 1000 ID



The dispersion unit and the electrical control unit can be set up up to 2 m apart from each other.

The return speed for container changeover is optimized on the RBG 1000 I and is faster than on the other RBG variants. It is only approx. 1 minute.

Optional operation with low pressure from 300 mbar absolute is possible.

The feedstock reservoirs with a 7, 10, 14, or 20 mm diameter are pressure-resistant.

For operation with low pressure, special pressure-resistant feedstock reservoirs are needed. Their piston is strongly connected to the feeding unit by a claw. This enables an undisturbed operation with low pressure. Old RBG models can be upgraded with this function by Palas®.

The 28 mm diameter feedstock reservoir is not pressure resistant, but can be used in the RBG 1000 ID when dosing in atmospheric conditions.

In the RBG 1000 D pressure-resistant version, compressed air is used as the disgerger gas. Operation with nitrogen or other inert gases is not permitted.

## BENEFITS

- Pressure resistant up to 3 barg overpressure
- Optional: negative pressure operation from 300 mbar absolute, remote control or computer control
- Highest short-term and long-term dosing consistency
- Disperses practically all non-cohesive dusts
- Easy exchange of different solids containers and dispersion lids
- Easy determination and adjustment of mass flow
- Pulse operation
- Easy cleaning of the unit
- Quick and easy operation
- Reliable function
- Low maintenance
- Reduces your operating costs

## APPLICATIONS

- All applications pressure-resistant up to 3 barg overpressure
- Dispersion of radioactive substances
- Dispersion of pharmaceutical powders
- Filter industry:
  - Determination of fractional separation efficiency
  - Determination of total separation efficiency
  - Long-term dusting
  - Filter media and ready-made filters
  - Dust removal filters
  - Vacuum cleaners and vacuum cleaner filters
  - Car interior filters
  - Engine air filters
- Calibration of particle measurement devices
- Flow visualization
- Inhalation tests
- Tracer particles for LDA, PIV, etc.
- Coating of surfaces

## DATASHEET

Particle size range	0.1 – 100 $\mu\text{m}$
Maximum particle number concentration	Ca. $10^7$ particles/ $\text{cm}^3$
Volume flow	0.5 – 5.0 $\text{m}^3/\text{h}$
Mass flow (particles)	0.04 – 430 g/h (with an assumed compacted density of 1 g/ $\text{cm}^3$ )
Filling height	70 mm
Filling quantity	2.7 g (reservoir $\varnothing$ = 7 mm), 5.5 g (reservoir $\varnothing$ = 10 mm), 10.8 g (reservoir $\varnothing$ = 14 mm), 22 g (reservoir $\varnothing$ = 20 mm), 43 g (reservoir $\varnothing$ = 28 mm)
Power supply	115 – 230 V, 50/60 Hz
Particle material	Non-cohesive powders and bulks
Dosing time	Several hours nonstop
Pre-pressure	4 – 8 bar
Carrier/dispersion gas	Air
Maximum counter pressure	0.2 barg
Compressed air connection	Quick coupling
Feed rate	5 – 700 mm/h
Reservoir inner diameter	7, 10, 14, 20, 28 mm

additional parameter on our website ...



Further information:  
<https://www.palas.de/product/rbg1000id>