RBG 2000



The RBG system disperses non-cohesive powders, e.g., mineral dusts, active pharmaceutical ingredients, pollen, etc., within the size range of < 100 μm and with a fine fraction of < 100 nm. Monolithic solid materials, e.g., blackboard chalk, are finely dispersed with optimal dosing constancy.The feedstock reservoirs of RBG 2000 are longer (fill level= 180 mm) than the feedstock reservoirs of RBG 1000. Also a reservoir with a bigger diameter is available. Thus, the dosing time with the same mass flow can be extended by more than a factor of 3. Mass flows of between approx. 200 mg/h and 560 g/h are dispersed with optimal dosing constancy.

Optional: Pressure-resistant up to 3 bar

Benefits

- Optimal short-term and long-term dosing constancy
- Double the dosing time in comparison with the RBG 1000
- Disperses virtually any non-cohesive dusts
- Easy to switch out different solid material reservoirs and dispersion covers
- Easy to determine and adjust the mass flow
- Able to adjust higher mass flows than the RGB 1000
- Pulse mode
- Easy to clean
- Quick and easy to operate
- Reliable function
- Low maintenance
- Reduces your operating expenses

Applications

- Filter industry
  - Determination of fractional separation efficiency
  - Determination of total separation efficiency
  - Long-term dusting
  - Filter media and assembled filters
  - Dust filters
- Calibrating particle measurement devices
- Flow visualization
- Inhalation experiments
- Tracer particles for LDV, PIV, etc.

Model Variations

...model available in additional variations

Particle size range	0.1 – 100 μm
Maximum particle number concentration	Ca. 10^7 particles/cm^3
Volume flow	40 – 80 Nl/min
Mass flow (particles)	1 – 560 g/h (with an assumed compacted density of 1 g/cm^3)
Filling height	180 mm
Filling quantity	36 g (reservoir Ø = 16 mm), 56 g (reservoir Ø = 20 mm), 110 g (reservoir Ø = 28 mm), 144 g (reservoir Ø = 32 mm)
Power supply	115 – 230 V, 50/60 Hz
Particle material	Non-cohesive powders and bulks
Dosing time	Several hours nonstop
Pre-pressure	4 – 8 bar
Carrier/dispersion gas	Random (generally air)
Maximum counter pressure	0.2 barg
Compressed air connection	Quick coupling
Feed rate	5 – 700 mm/h
Reservoir inner diameter	16, 20, 28, 32 mm
Aerosol outlet connection	Dispersion cover type A: $Ø_{inside}$= 5 mm, $Ø_{outside}$ = 8 mm; Dispersion cover type D: $Ø_{inside}$= 5 mm, $Ø_{outside}$ = 8 mm
Dispersion lid	Type A, Type D
Dimensions	1.160 • 530 • 500 mm (H • B • T)
Weight	Approx. 40 kg