UF-CPC 200



The UF-CPC 200 is a butanol-based nanoparticle counter with high efficiency. It measures the number concentrations of ultrafine particles (UFP) in aerosols. Model 200 is designed for concentrations up to $2 \cdot 10^6$ particles/cm^3. This makes it especially suitable for low dilution measurement of high aerosol concentrations from particle generators, exhaust gas, or ambient air of exposed and heavily polluted areas. In nephelometer mode, measurements up to $2 \cdot 10^7$ particles/cm^3 are possible. The counter can be easily combined with the Palas size classifiers and thus directly allows the measurement of highly concentrated and size-selected aerosols, e.g., for efficiency measurement of HEPA filter media in test stands.

The patented evaporator and condensation module is maintenance-free. This allows continuous operating times of up to one year.

Benefits

- Intuitive user interface with sophisticated software for data analysis
- Unlimited network compatibility that supports remote control and data storage on the Internet
- Visualization of all operating and measurement data
- Integrated interface for process control applications
- Lower detection efficiency D50 adjustable to 10 nm (others on request)

Applications

- Aerosol research
- Testing of filters and air purifiers
- Environmental measurements
- Occupational exposure and workplace safety studies
- Inhalation and health effects studies
- Process monitoring
- Printer emission studies

Features

- Automatic measurement data storage
- Measurement of the particle size distribution of condensed particles for quality assurance
- Integrated pump
- Integrated computer with 7″ touchscreen

DATASHEET

Measuring principle	Condensation of ultrafine particles with optical measurement of concentrations
Measurement range (number C_N)	$2 \cdot 10^6$ particles/cm^3 (single count mode)
Measurement range (size)	4 – >3,000 nm
Volume flow	0.9 L/min (butanol) 0.3–1 L/min (adjustable for research applications) (others on request)
Time resolution	Min. 1s
Interfaces	USB, Ethernet (LAN), weather station/butanol level sensor, RS-232, T/rH sensor
User interface	Touchscreen, 800 • 480 pixel, 7″ (17.78 cm)
Protocols	UDP, UIDEP, B/H, MODBUS TCP/RTU, ASCII TCP/Seriell
Data logger storage	4 GB
Software	PDAnalyze
Detection efficiency (at low particle size)	D50 = 10 ± 1 nm (others on request); D90 < 20 nm, D95 @ 40 nm ± 10 nm, D90 @ 1000 nm ± 100 nm
Data acquisition	Digital, 20 MHz processor, 256 raw data channels
Light source	LED
Housing	Tabletop device
Power supply	90 – 264 V, 50/60 Hz
Power consumption	Average power consumption: 40 W
Installation conditions	+10 – +30 °C (others on request)
Accuracy	5 % (single count mode)
Response time	t_{90} < 2.8 s, t_{90-10} < 2.0 s
Working fluid	n-Butanol (>99.5%)
Dimensions	290 • 240 • 350 mm (H • W • D)
Weight	Approx. 10 kg
Resolution	Min. 1s
Data Management	Prepared for connection to the Palas Cloud MyAtmosphere (“MyAtmosphere-ready”)

NORMS AND CERTIFICATES

ISO 27891:2015