U-SMPS 2050 X/2100 X/2200 X



A soft X-ray source as a neutralizer is already integrated. The advantage instead of a radioactive neutralization (for example, with Kr-85) is that there is no need to follow requirements during transportation.

OPERATION PRINCIPLE

BENEFITS

- Particle size distributions from 4 nm to 1.2 μm
- Continuous and fast-scanning principle of measurement
- High resolution in up to 128 size classes/decade
- Suitable for concentrations of up to10^8 particles/cm^3
- Universally connects to DMAs and nanoparticle counters from other manufacturers
- Graphic display of measurement values
- Intuitive operation using 7″ touchscreen and GUI
- Integrated data logger
- Supports multiple interfaces and remote access
- Low maintenance

* Please contact Palas® for further details.

NORMS AND CERTIFICATES

ISO 15900:2010, ISO 27891:2015, CEN/TS 17434:2020

DATASHEET

Measurement range (number C_N)	0 – 10^8 particles/cm^3
Measurement range (size)	4 – 1,200 nm
Volume flow	0.5 – 3 l/min
Volume flow (sheath air)	2.5–20 l/min (others on request)
Size channels	Max. 256 (128/decade)
Interfaces	USB, Ethernet (LAN), AUX, RS-232 (CPC only)
User interface	Touchscreen, 800 • 480 pixel, 7″ (17.78 cm)
Data logger storage	4 GB
Software	PDAnalyze
Power supply	90 – 264 V, 50/60 Hz
Installation conditions	+10 – +30 °C (others on request)
Adjustment range (voltage)	1 – 10,000 V(UP and DOWN scan possible)
Neutralizer	X-ray (XRC 049)
Data Management	Prepared for connection to the Palas Cloud MyAtmosphere (“MyAtmosphere-ready”); Internet access and separate registration required. The MyAtmosphere terms of use apply.

APPLICATIONS

- Filter test
- Aerosol research
- Environmental and climatic studies
- Inhalation experiments
- Interior and workplace measurements

Mehr Informationen:
https://www.palas.de/en/product/usmps2050x$_2$100x