

U-SMPS 2050 X/2100 X/2200 X



A soft X-ray source as a neutralizer is already integrated. The advantage instead of a radioactive neutralization (for example, with Kr-85) is that there is no need to follow requirements during transportation.

OPERATION PRINCIPLE

BENEFITS

- Particle size distributions from 4 nm to 1.2 μm
- Continuous and fast-scanning principle of measurement
- High resolution in up to 128 size classes/decade
- Suitable for concentrations of up to 10^8 particles/ cm^3
- Universally connects to DMAs and nanoparticle counters from other manufacturers
- Graphic display of measurement values
- Intuitive operation using 7" touchscreen and GUI
- Integrated data logger
- Supports multiple interfaces and remote access
- Low maintenance
- Reliable function
- Reduces your operating expenses

* Please contact Palas® for further details.

DATASHEET

Measurement range (number C_N)	
	0 – 10 ⁸ particles/cm ³
Measurement range (size)	4 – 1,200 nm
Volume flow	0.5 – 3 l/min
Volume flow (sheath air)	2.5 – 14 l/min
Size channels	Max. 256 (128/decade)
Interfaces	USB, Ethernet (LAN), AUX, RS-232 (CPC only)
User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Data logger storage	4 GB
Software	PDAnalyze
Installation conditions	+10 – +30 °C (others on demand)
Adjustment range (voltage)	1 – 10,000 V(UP and DOWN scan possible)
Data Management	Prepared for connection to the Palas Cloud MyAtmosphere ("MyAtmosphere-ready"); internet access and separate registration required. MyAtmosphere terms and conditions of use apply.

APPLICATIONS

- Filter test
- Aerosol research
- Environmental and climatic studies
- Inhalation experiments
- Interior and workplace measurements



Mehr Informationen:

<https://www.palas.de/product/usmps2050x2100x2200x>