



MODEL VARIATIONS



welas[®] digital 3000 H
With heating regulation up to 250 °C for welas[®] aerosol sensors



welas[®] digital 3000 HP
With automatic regulation of sampling volume flow by the aerosol sensors welas[®] under overpressure up to 10 bar or in temperatures to 120 °C



welas[®] digital 3000 P
With automatic regulation of sampling volume flow by the aerosol sensors welas[®] under overpressure up to 10 bar

DESCRIPTION

The **welas[®] digital 3000** is a flexible, powerful and economical light-scattering spectrometer system with two **aerosol sensors¹**, which determines particle concentration and size precisely and reliably.

Unique are up to four measuring ranges in only one device:

- 0.2 μm – 10 μm
- 0.3 μm – 17 μm
- 0.6 μm – 40 μm
- 2 μm – 100 μm (additionally for sensors 2300 and 2500).

welas[®] digital 3000 is famous for up to 128 size channels per measuring range and a concentration range from < 1 particle/cm³ to 10⁶ particles/cm³.

On the new **welas[®] digital 3000**, two **welas[®]** sensors are supplied with one light source and the scattered light pulses are detected by a photomultiplier. This enables a quasi-simultaneous particle measurement at two sampling locations that are up to 100 meters apart.

The quasi-simultaneous particle size and particle quantitative determination offers particular advantages for characterising separators with fluctuating raw gas concentrations.

With the **welas[®] digital 3000** the user effectively has two scattered-light spectrometers in one device with the same device characteristics:

- Particle size resolution capability
- Particle size classification accuracy
- Counting efficiency
- Zero counting rate

The various **welas[®]** sensors are characterized by a particularly good conformity of counting efficiency and particle size resolution (see data sheet: **welas[®]** sensors).

Opto-mechanical switching

Using opto-mechanical switching, the two sensors that are connected can be easily controlled. The sensors are controlled automatically with the software.

The particular advantage over a manual measurement selector switch:

- Faster change of the measurement location
- No deposits in sampling lines
- Long service life; no wear of the seals due to dust particles

The **welas[®] digital 3000** is characterized by its optical fibre technology. The **welas[®]** sensor is connected via a fiber optic cable with a length up to 30 m with the **welas[®]** digital control unit.

This leads to a minimization of particle losses in long sampling lines by simply installing the sensor directly at the sampling location.

Connection via fiber-optic cable allows the **welas[®] 2000** and **2000 P** series sensors to be easily connected to the control and evaluation unit and interchanged as required.

¹aerosol sensors: <https://www.palas.de/en//product/aerosolsensorswelas2000>

The welas[®] sensors are equipped with different sized measurement volumes. This allows adaptation of the measuring device to the particle concentration present in the application, such that a high counting rate can be achieved with a short measuring time.

The aerosol sensors allow reliable measurement in the concentration range from < 1 particle/cm³ up to 10⁶ particles/cm³.

The welas[®] digital is based on scattered-light analysis on a single particle. With the new welas[®] digital, the special advantages of the well-known and internationally acclaimed welas[®] system are combined with new and fast digital individual signal processing and coincidence correction is enabled.

The high size classification accuracy and the high size resolution are guaranteed by the following special feature (see Graph 1):

- White light and 90° light-scattering detection
⇒ **Unambiguous calibration curve**
- Patented T-aperture
⇒ **No border zone error**
- New digital individual signal processing
⇒ **Coincidence detection and correction of the individual signal making it possible to measure in higher concentrations**

The welas[®] digital measurement technology

welas[®] digital offers a new, fast 20 MHz signal processing processor, which analyses the progression of each particle signal. This makes it possible to recognise coincidental events in light scattering measurement technology at the individual signal and correct them (according to Dr. Umhauer / Prof. Dr. Sachweh).

This way it is possible to increase the maximum concentration limit up to 10⁶ particles/cm³ (welas[®] 2070 sensor).

Also in low concentrations < 1 particle/cm³ with the welas[®] 2500 sensor, this leads to a higher measuring accuracy.

High classification accuracy, high resolution capability and a high counting efficiency are the prerequisite for unambiguous particle measurement.




Fig. 1: Resolution capability and classification accuracy

The welas[®] digital is characterized by its very high counting efficiency starting from 0.2 μm!




Fig. 2: Example with sensor

The welas[®] PDControl digital software

The welas[®] digital is controlled via a laptop using the PDControl software. The software allows particle measurements and calibration of the measurement device.

In addition, the measurements can be analyzed and compared in detail with a temporal resolution down to 10 ms.

BENEFITS

- Measuring range of 0.2 to 100 μm (4 measuring ranges selectable in one device)
- Up to four measuring ranges in only one device:
 - 0,2 μm – 10 μm
 - 0,3 μm – 17 μm
 - 0,6 μm – 40 μm
 - 2 μm – 100 μm (additionally for sensors 2300 and 2500)
- Up to 128 size channels per measuring range
- Concentration range of 1 particle/ cm^3 up to 10^6 particles/ cm^3
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency rate starting at 0.2 μm (see Graph 2)
- High temporal resolution down to 10 ms
- Optical fibre technology
- Measurement in potentially explosive environment
- Long service life of the light source of 2000 h
- Extensive PDControl

- Simple operation
- Calibration, cleaning and lamp replacement can all be performed independently by the customer
- Low maintenance
- Reliable function
- Reduces your operating expenses

DATASHEET

Measuring principle	Optical light-scattering
Measurement range (number C_N)	$< 1 \cdot 10^6$ particles/cm ³
Measurement range (size)	0.2 – 10 μm , 0.3 – 17 μm , 0.6 – 40 μm , 2 – 100 μm
Size channels	Max. 64/decade
Volume flow	5 l/min
Time resolution	≥ 10 ms
Thermodynamic conditions	+10 – +40 °C, -100 – 50 mbar
Data acquisition	Digital, 20 MHz processor, 256 raw data channels
Light source	Xenon arc lamp 35 W
User interface	Laptop
Housing	Table housing, optional: with mounting brackets for rack-mounting
Weight	Control unit: approx. 18 kg, sensor: approx. 2.8 kg
Software	PDControl
Installation conditions	+5 – +40 °C (control unit)
Interfaces	USB
Power supply	115 – 230 V, 50/60 Hz
Dimensions	185 • 450 • 315 mm (H • W • D) (19")

APPLICATIONS

- Abscheidegradbestimmung von KFZ Innenraumfiltern, Motorluftfiltern, Raumluftfiltern, Druckluftfiltern, Staubsaugerfiltern, abreinigbaren Filtern, Elektrofiltern, Ölabscheidern, Kühlschmierstoffabscheidern, Nassabscheidern, Zyklonen und anderen Abscheidern
- Isotherme und isobare Partikelgrößen- und Mengenbestimmung, z. B. in der Automobil-, Chemie-, Pharma- und Lebensmittelindustrie
- Untersuchung schneller, instationärer Prozesse
- Test von Rauchmeldern
- Partikelmessung zur Wolkenbildung
- Emissionsmessungen
- Atemfunktion: Inhalat / Exhalat (Partikelgröße und -anzahl)



Mehr Informationen:
<https://www.palاس.de/product/welasdigital3000>