

# DLB 2000



The DLB 2000, well established in practice, ensures fully automated regulation of rel. humidity with maximum stability. The input of the required rel. humidity and setting of the temperature take place using a touchscreen display.

## 优势

- Adjustable relative humidity from 20 to 80 %
- Highest stability of relative humidity 0.2 %
- Easy handling by touch screen
- External control analogue 0 - 5 V
- Huge water supply tank
- Easy refilling of water
- Reliable function
- Low maintenance
- Reduces your operating costs!

## 应用领域

- Accurate regulation of rel. humidity for test rigs, e.g.
  - filter testing
  - active carbon filter testing
  - bioaerosol measuring device testing
  - dust measuring device testing
  - etc.
- Conditioning of the dispersion air for the RBC 1000 and RBC 2000 dust dispersers (the instruction manual of the dust dispersers has to be followed).
- Laboratory experiments with special requirements for the stability of rel. humidity.

## 技术数据

体积流量	10 – 60 NI/min (others on request)
接口	Analog (0 – 5 V (set point)0 – 5 V (measured humidity))
电源	115 – 230 V, 50/60 Hz
Maximum counter pressure	0.5 barg overpressure
Luftfeuchteregelung	20% – 80% (+/- 0.2% at 23 °C)
Water supply	1 l deionised water
Dimensions	280 • 320 • 460 mm (H • W • D)
重量	Approx. 16 kg