FIDAS® 200 E

The Fidas® 200 E version shown here consists of a 19″ plug-in unit and a remote sensor (connection length 3 m, other sizes on request) for use in air-conditioned monitoring stations (temperature range 5 - 40 °C). The remote sensor, flanged to the lower end of the aerosol sampling tube, greatly simplifies installation in stations with an existing roof penetration. Variants of the Fidas® 200 E are the basic Fidas® 200 and the Fidas® 200 S (with stainless steel weatherproof housing) designed for outdoor installation.

工作原理

优势

- High flexibility for installation due to separation of sensor unit and control unit
- Type-approved and certified according to latest EN requirements (EN 15267)
- Continuous and simultaneous real-time measurement of multiple PM values
- Additional information on particle number concentration and particle size distribution
- Long service life
- Low maintenance
- External check of calibration on site possible
- Intuitive and easy to operate
- Reliable function, very high data availability (> 99 %)
- Permanent monitoring of status, among others online monitoring of calibration
- No radioactive material and no consumables
- Low energy consumption

标准和证书

VDI 4202-1, VDI 4203-3, EN 12341, EN 14907, EN 16450, EU-Äquivalenzleitfaden, EN 15267-1/-2, ISO 21501-1, LCSQA (2023)

技术数据

测量原理	Optical light scattering at single particles, 90° sideways scattering
报告数据	PM_1, $PM_{2.5}$, PM_4, PM_{10}, TSP, C_N, particle size distribution, ambient pressure, ambient temperature, rel. ambient humidity
测量范围(数量浓度)	0–20.000 颗粒/cm^3
测量范围(粒径)	0.178 - 17.8 μm (additional: 0.4 - 40μm, 1-100μm)
测量范围(质量)	0–10.000 $\mu g/m^3$
测量不确定性	9.7 % for $PM_{2.5}$, 7.5 % for PM_{10}(expanded measurement uncertainty according to EN 16450, 450, (see Qal1.de))
体积流量	4.8 Nl/min (25°C, 1013 hPa) < +/- 1% (MFC-controlled diaphragm pump)
Size channels	64 (32/decade)
Time resolution	1s - 24h variable adjustable
接口	USB, Ethernet (LAN), RS-232, Wi-Fi (Dongle), digital
User interface	Touchscreen, 800 • 480 pixel, 7″ (17.78 cm)
Protocols	UIDEP, UDP, ASCII, MODBUS, Bayern-Hessen
Data logger storage	Capacity for 2 years continuous operation at 60 s storage interval
Data acquisition	Max. 256 raw data channels (32 size channels/decade)
Light source	Polychromatic LED
外壳	19″, 4U (desktop and rack-mount housing) - Separate sensor
Operating system	Windows 10 IoT (LTSA)
电源	115 – 230 V, 50/60 Hz
Installation conditions	Operating temperature: +5–+40 °C, operating humidity: 0–100% (non-condensing)
Sampling head	Sigma head (non-selective passive collector)
Dimensions	Control unit: 450 • 320 • 180,5 mm (H • W • D) (19″), external sensor: 240 • 180 • 120 mm (H • W • D) (19″)
重量	Control unit: 9.3 kg, sample head: 2.25 kg, sample tube: 4.5 kg
Sampling system	Drying of the aerosol by IADS (Intelligent Aerosol Drying System)
Noise emission	< 70 dB(A)
Resolution	0.1 $\mu g/m^3$
Power consumption	Normal operation: 60 W, max. 200 W
Data Management	Prepared for connection to the Palas Cloud MyAtmosphere (“MyAtmosphere-ready”)
Repeatability	3 %

应用领域

- Regulatory pollution control in monitoring networks
- Ambient air monitoring campaigns
- Long-term studies
- Emission source attribution
- Emission dispersion studies (e.g. fires, volcanoes)

Mehr Informationen:
https://www.palas.de/zh/product/fidas200e