MFP 3000 G







Version MFP 3000 G is especially tailored to the requirements of the ISO 16890 measurement procedure.

优势

- Virtually simultaneous particle measurement in upand down stream
- · High reproducibility of the testing method
- Easy use of different test aerosols, e.g. SAE Fine and Coarse, NaCl/KCl, DEHS
- Highest raw gas concentrations of up to > 70 mg/m³ (ISO Fine) or > 300 mg/m³ (ISO Coarse) with measurement of the fraction separation efficiency for loading tests
- Sequence programs for pressure loss measurements, measurements of fraction separation efficiency and burden measurements
- Short set-up times
- Cleaning and calibration can be performed autonomously by the customer
- Easy use of the measurement technology components – even in other applications
- Mobile setup, easy to move on castors
- Validation of the clear function during acceptance testing

特点

- Measurement of Cn max= 4x104 particles/cm3 without dilution
- Measurement of fractional efficiency and pressure loss vs. volume flow
- Use of the Promo® 3000 aerosol spectrometer
- Connection of the sensors in raw and clean gas
- Customized filter adapters and adaptations in the air duct possible
- On-site calibration and adjustment (particle size and volume flow)
- Checking the volume flow and pressure loss using a

应用领域

- Testing of filter media and small filter elements in product development and during production monitoring.
- Testing option based on ISO 16890 (General ventialtion air filters), the test procedure according to ASHRAE 52.2 or EN 779 is optinal available.

perforated plate https://www.palas.de/zh/product/mfp3000g



技术数据

气溶胶	Dusts (e.g., SAE dusts), salts (e.g., NaCl, KCl), liquid aerosols (e.g., DEHS)	滤材测试面积	100 cm ²
测量范围(粒径)	0.2 – 40 μm	测量范围(质量)	Up to 1,000 mg/m 3 (depending on the version)
体积流量	$1-35~\mathrm{m}^3/\mathrm{h}$ - suction mode	Differential pressure measurement	0 – 1,200 Pa selectable, 0 – 2,500 Pa selectable, 0 – 5,000 Pa selectable
Inflow velocity	5 cm/s – 1 m/s (others on request)	Compressed air supply	6 – 8 bar
Dimensions	2.500 • 680 • 1.550 mm (H • B • T)		

标准和证书

ISO 5011, ISO/TS 19713, DIN 71460, ISO 11155-1, EN 779, ASHARE 52.2, ISO 16890