

# MFP 3000 M



Version MFP 3000 M is especially tailored to the requirements of the ISO 5011 and ISO TS 19713-2 measurement procedures.

## BENEFITS

- Virtually simultaneous particle measurement in the raw gas and clean gas
- Particle size measurements from 0.2 – 40  $\mu\text{m}$
- Measurement of  $C_{n \text{ max}} = 10^6$  particles/ $\text{cm}^3$  without dilution
- Internationally comparable measurement results
- High reproducibility of the testing method
- Easy use of different test aerosols, e.g. SAE Fine and Coarse, NaCl/KCl, DEHS
- Highest raw gas concentrations of up to > 1000  $\text{mg}/\text{m}^3$  (ISO Fine) or > 5000  $\text{mg}/\text{m}^3$  (ISO Coarse) with measurement of the fraction separation efficiency for burden tests
- Sequence programs for pressure loss measurements, measurements of fraction separation efficiency and burden measurements
- Easy to operate
- Short set-up times
- Cleaning and calibration can be performed by the customer
- Easy use of the measurement technology components – even in other applications
- Mobile setup, easy to move on castors
- Validation of the clear function of individual components and the overall system during pre-delivery acceptance testing and upon delivery
- Low-maintenance

## APPLICATIONS

- Testing of filter media and small filter elements in product development and during production monitoring.
- Testing based on ISO 5011 (engine air intake filters)

## 特点

- Measurement of fractional efficiency and pressure loss vs. volume flow
- Use of the Promo<sup>®</sup> 3000 aerosol spectrometer
- Connection of the sensors in raw and clean gas
- Customized filter adapters and adaptations in the air duct possible

## DATASHEET

气溶胶	Dusts (e.g., SAE dusts), salts (e.g., NaCl, KCl), liquid aerosols (e.g., DEHS)	滤材测试面积	100 cm <sup>2</sup>
测量范围(粒径)	0.2 – 40 µm	测量范围(质量)	Up to 1,000 mg/m <sup>3</sup> (depending on the version)
体积流量	1 – 35 m <sup>3</sup> /h - suction mode	Differential pressure measurement	0 – 1,200 Pa selectable, 0 – 2,500 Pa selectable, 0 – 5,000 Pa selectable
Inflow velocity	5 cm/s – 1 m/s (others on request)	Compressed air supply	6 – 8 bar
Dimensions	2.500 • 680 • 1.550 mm (H • B • T)		

## 标准和证书

ISO 5011, ISO/TS 19713, DIN 71460, ISO 11155-1, EN 779, ASHARE 52.2, ISO 16890