MFP 4000







The MFP filter test rig is a modular filter testing system for flat filter media and small mini-filters.

This enables you to determine the pressure loss curve on the medium without a dust coating, fraction separation efficiency, orburden and fraction separation efficiency during application of the burdenand the gravimetric separation efficiency within shortest times – reliably and therefore cost-effectively.

The MFP 4000 operates in suction mode. This ensures a particularly uniform formation of the dust cake even at high inflow speeds.

With the FTControl test rig software of the MFP 4000, the aerosol spectrometer Promo[®] 1000/2000 is used for clear and reliable determination of the aerosol concentration and particle size and therefore clear determination of the fraction separation efficiency.

优势

- Simultaneous particle measurement in the raw gas and clean gas
- Particle size measurements from $0.2 40 \mu m$
- Measurement of $C_{n \text{ max}} = 10^6 \text{ particles/cm}^3 \text{ without dilution}$
- · Internationally comparable measurement results
- High reproducibility of the testing method
- Easy use of different test aerosols, e.g. SAE Fine and Coarse, NaCl/KCl, DEHS
- Highest raw gas concentrations of up to > 1000 mg/m³ (ISO Fine) or > 5000 mg/m³ (ISO Coarse) with measurement of the fraction separation efficiency for burden tests
- Sequence programs for pressure loss measurements, measurements of fraction separation efficiency and burden measurements
- · Easy to operate
- · Short set-up times
- Cleaning and calibration can be performed by the customer
- Easy use of the measurement technology components even in other applications
- Mobile setup, easy to move on castors
- Validation of the clear function of individual components and the overall system during pre-delivery acceptance testing and upon delivery https://www.palas.de/zh/product/mfp4000
 Low-maintenance

应用领域

- For filter media and small filter elements
- Product development and during production monitoring
- Testing based on ISO 11155-1 / DIN 71460-1 (cabin air filters)
- Testing based on ISO 5011 (engine pre-air filters)
- Testing based on ISO 16890 (room air filters)
- Other standards in various versions

版本: 2025年10月05日 页码1中的2



技术数据

气溶胶	Dusts (e.g., SAE dusts), salts (e.g., NaCl, KCl), liquid aerosols (e.g., DEHS)	滤材测试面积	100 cm ²
测量范围(粒径)	0.2 – 40 μm	测量范围(质量)	Up to 1,000 mg/m³ (depending on the version)
体积流量	$1-35~\mathrm{m}^3/\mathrm{h}$ - suction mode	Differential pressure measurement	0 – 1,200 Pa selectable, 0 – 2,500 Pa selectable, 0 – 5,000 Pa selectable
Inflow velocity	5 cm/s – 1 m/s (others on request)	Compressed air supply	6 – 8 bar

标准和证书

ISO 11155-1 / DIN 71460-1, ISO 5011, ISO 16890