

# PLG 2000 HS



In addition to a built-in heating unit, the PLG 2000 HS generator is equipped with an automatic refill unit.

## 优势

- Excellent short-term and long-term dosing constancy
- Best reproducibility with respect to particle size distribution and particle concentration
- Large mass volume range (very low and very high)
- Robust design (optionally resistant against chemically aggressive liquids)
- Compact and light
- Easy to operate, proven in industrial applications
- Reliable function
- Low maintenance

## 应用领域

- Filter industry/oil separators
  - Determination of separation efficiency
  - Determination of fractional separation efficiency
  - Loading test
- Test of cooling lubricant separators
- Comparison of particle measurement devices
- Tracer particles
- Flow visualization

## 技术数据

体积流量	10 – 35 l/min
Mass flow (particles)	< 20 g/h (white oil)
Filling quantity	300 ml
电源	115 – 230 V, 50/60 Hz
Aerosol outlet connection	$\varnothing_{\text{inside}} = 9 \text{ mm}, \varnothing_{\text{outside}} = 12 \text{ mm}$
Mean particle diameter (number)	0.4 $\mu\text{m}$ (DEHS)
Dimensions	300 • 330 • 280 mm (H • W • D)
重量	Approx. 12 kg
Special features	Heatable up to 100°C, with automatic refilling unit