## **RBG 1000 SD**







This device disperses particles at positive pressure values of up to 3 bar and can also use nitrogen, in addition to air, as the dispersing gas. Optional operation with low pressure from 300 mbar absolute is possible. The 7-, 10-, 14- or 20-mm feed stock reservoirs are pressure-resistant. For operation with low pressure special pressure-resistant feed stock reservoirs are needed. Their piston is strongly connected to the feeding unit by a claw. This enables an undisturbed operation with low pressure.

The solid material reservoir with a diameter of 28 mm is not pressure-resistant, but can be used with the RBG 1000 SD under atmospheric conditions.

## 优势

- Pressure-resistant up to 3 barg overpressure
- Optional:Low pressure operation from 300 mbar absolute
- · Nitrogen as dispersing gas
- Optional: Remote control or computer-controlled

## 应用领域

- All applications pressure resistant up to 3 bar overpressure
- Testing of compressed air filters
- Filter industry:
  - Determination of fractional separation efficiency
  - Determination of total separation efficiency
  - Long-term dusting
  - Filter media and ready-made filters
  - Dust removal filters
  - Vacuum cleaners and vacuum cleaner filters
  - Car interior filters
  - Engine air filters
- Calibration of particle measurement devices
- Flow visualization
- · Inhalation tests
- Tracer particles for LDA, PIV, etc.
- Coating of surfaces



## 技术数据

粒径范围	$0.1 - 100 \ \mu m$	颗粒物最大数量浓度	Ca. 10 <sup>7</sup> particles/cm <sup>3</sup>
体积流量	0.5 – 5.0 m <sup>3</sup> /h	Mass flow (particles)	$0.04-430$ g/h (with an assumed compacted density of $1$ g/cm $^3$ )
Filling height	70 mm	Filling quantity	2.7 g (reservoir $\emptyset$ = 7 mm), 5.5 g (reservoir $\emptyset$ = 10 mm), 10.8 g (reservoir $\emptyset$ = 14 mm), 22 g (reservoir $\emptyset$ = 20 mm), 43 g (reservoir $\emptyset$ = 28 mm)
电源	115 – 230 V, 50/60 Hz	Particle material	Non-cohesive powders and bulks
Dosing time	Several hours nonstop	Pre-pressure	4 – 8 bar
Carrier/dispersion gas	Air, nitrogen	Maximum counter pressure	0.2 barg
Compressed air connection	Quick coupling	Feed rate	5 – 700 mm/h
Reservoir inner diameter	7, 10, 14, 20 mm	Aerosol outlet connection	Dispersion cover type A: $\mathcal{O}_{inside} = 5$ mm, $\mathcal{O}_{outside} = 8$ mmDispersion cover type B: $\mathcal{O}_{inside} = 3.6$ mm, $\mathcal{O}_{outside} = 6$ mmDispersion cover type: $\mathcal{O}_{inside} = 2.5$ mm, $\mathcal{O}_{outside} = 6$ mm
Dispergierdeckel	Type A, type B, type C, type D	Dimensions	465 • 320 • 200 mm (H • W • D)
重量	Approx. 19 kg		