

UF-CPC 100



The UF-CPC 100 is a butanol-based nanoparticle counter with high efficiency. It measures the number concentrations of ultrafine particles (UFP) in aerosols. Model 100 is designed for concentrations up to 10^5 particles/cm³. This makes it very suitable for determining the particle concentrations of aerosols, not only in ambient air but also for synthetically produced aerosols, for example, for measuring the efficiency of filter media. In nephelometer mode, measurements up to $2 \cdot 10^7$ particles/cm³ are possible. The counter can be easily combined with the Palas size classifiers (Scanning Mobility Particle Spectrometer / Mobility Particle Size Spectrometer).

The patented evaporator and condensation module is maintenance-free. This allows continuous operating times of up to one year.

优势

- Intuitive user interface with sophisticated software for data analysis
- Unlimited network compatibility that supports remote control and data storage on the Internet
- Visualization of all operating and measurement data
- Integrated interface for process control applications
- Lower detection efficiency D50 adjustable to 10 nm (others on request)

应用领域

- Aerosol research
- Testing of filters and air purifiers
- Environmental measurements
- Workplace exposure and occupational safety studies
- Studies concerning inhalation and health impacts
- Process control
- Printer emission studies

特点

- Expandable to U-SMPS spectrometer
- Automatic measurement data storage
- Measurement of the particle size distribution of condensed particles for quality assurance
- Integrated pump
- Integrated computer with 7" touchscreen

技术数据

测量原理	Condensation of ultrafine particles, optical sensor for determining the number concentration and size distribution of the condensed particles
测量范围(数量浓度)	10^5 particles/cm ³ (single count mode), $10^5 - 10^7$ particles/cm ³ (nephelometric mode)
测量范围(粒径)	4 – 5,000 nm
体积流量	0.9 L/min (butanol) 0.3–1 L/min (adjustable for research applications) (others on request)
Time resolution	Min. 1s
接口	USB, Ethernet (LAN), weather station/butanol level sensor, RS-232, T/rH sensor
User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Protocols	UDP, UIDEP, B/H, MODBUS TCP/RTU, ASCII TCP/Seriell
Data logger storage	4 GB
软件	PDAnalyze
Detection efficiency (at low particle size)	D50 = 10 ± 1 nm (others on request); D90 < 20 nm, D95 @ 40 nm \pm 10 nm, D90 @ 1000 nm \pm 100 nm
Data acquisition	Digital, 20 MHz processor, 256 raw data channels
Light source	LED
外壳	Tabletop device
电源	115 – 230 V, 50/60 Hz
Power consumption	Average power consumption: 40 W
Installation conditions	+10 – +30 °C (others on request)
Accuracy	5% (single count mode), 10% (nephelometric mode)
Response time	$t_{90} < 2.8$ s, $t_{90-10} < 2.0$ s
Working fluid	n-Butanol (>99.5%)
Dimensions	290 • 240 • 350 mm (H • W • D)
重量	Approx. 10 kg
Resolution	Min. 1s
Data Management	Prepared for connection to the Palas Cloud MyAtmosphere ("MyAtmosphere-ready")

标准和证书

ISO 27891:2015