

UF-CPC 200



The UF-CPC 200 is a butanol-based nanoparticle counter with high efficiency. It measures the number concentrations of ultrafine particles (UFP) in aerosols. Model 200 is designed for concentrations up to $2 \cdot 10^6$ particles/cm³. This makes it especially suitable for low dilution measurement of high aerosol concentrations from particle generators, exhaust gas, or ambient air of exposed and heavily polluted areas. In nephelometer mode, measurements up to $2 \cdot 10^7$ particles/cm³ are possible. The counter can be easily combined with the Palas size classifiers and thus directly allows the measurement of highly concentrated and size-selected aerosols, e.g., for efficiency measurement of HEPA filter media in test stands.

The patented evaporator and condensation module is maintenance-free. This allows continuous operating times of up to one year.

优势

- Intuitive user interface with sophisticated software for data analysis
- Unlimited network compatibility that supports remote control and data storage on the Internet
- Visualization of all operating and measurement data
- Integrated interface for process control applications
- Lower detection efficiency D50 adjustable to 10 nm (others on request)

应用领域

- Aerosol research
- Testing of filters and air purifiers
- Environmental measurements
- Occupational exposure and workplace safety studies
- Inhalation and health effects studies
- Process monitoring
- Printer emission studies

特点

- Automatic measurement data storage
- Measurement of the particle size distribution of condensed particles for quality assurance
- Integrated pump
- Integrated computer with 7" touchscreen

技术数据

| | |
|---|---|
| 测量原理 | Condensation of ultrafine particles with optical measurement of concentrations |
| 测量范围(数量浓度) | $2 \cdot 10^6$ particles/cm ³ (single count mode) |
| 测量范围(粒径) | 4 – 5,000 nm |
| 体积流量 | 0.9 L/min (butanol) 0.3–1 L/min (adjustable for research applications) (others on request) |
| Time resolution | Min. 1s |
| 接口 | USB, Ethernet (LAN), weather station/butanol level sensor, RS-232, T/rH sensor |
| User interface | Touchscreen, 800 • 480 pixel, 7" (17.78 cm) |
| Protocols | UDP, UIDEP, B/H, MODBUS TCP/RTU, ASCII TCP/Seriell |
| Data logger storage | 4 GB |
| 软件 | PDAnalyze |
| Detection efficiency (at low particle size) | D50 = 10 ± 1 nm (others on request); D90 < 20 nm, D95 @ 40 nm \pm 10 nm, D90 @ 1000 nm \pm 100 nm |
| Data acquisition | Digital, 20 MHz processor, 256 raw data channels |
| Light source | LED |
| 外壳 | Tabletop device |
| 电源 | 90 – 264 V, 50/60 Hz |
| Power consumption | Average power consumption: 40 W |
| Installation conditions | +10 – +30 °C (others on request) |
| Accuracy | 5 % (single count mode) |
| Response time | $t_{90} < 2.8$ s, $t_{90-10} < 2.0$ s |
| Working fluid | n-Butanol (>99.5%) |
| Dimensions | 290 • 240 • 350 mm (H • W • D) |
| 重量 | Approx. 10 kg |
| Resolution | Min. 1s |
| Data Management | Prepared for connection to the Palas Cloud MyAtmosphere ("MyAtmosphere-ready") |

标准和证书

ISO 27891:2015