

UF-CPC 50



The UF-CPC 50 is a butanol-based nanoparticle counter with high efficiency. It measures the number concentrations of ultrafine particles (UFP) in aerosols. Model 50 is designed for concentrations of up to 10^4 particles/cm³. Thus, it is ideally suited for measuring the lowest concentrations alone or as part of an overall system for measuring the size distribution and concentration of, e.g., synthetically produced aerosols (Scanning Mobility Particle Spectrometer / Mobility Particle Size Spectrometer).

The patented evaporator and condensation module is maintenance-free. This allows continuous operating times of up to one year.

优势

- Full flow analysis, no internal flow splitting
- Intuitive user interface with sophisticated software for data analysis
- Unlimited network compatibility that supports remote control and data storage on the Internet
- Visualization of all operating and measurement data
- Integrated interface for process control applications
- Lower detection efficiency D50 adjustable to 10 nm (others on request)

应用领域

- Aerosol research
- Combustion engine emission testing
- Brake dust emission testing
- Test of filters and air cleaners
- Environmental measurements
- Studies on working place pollution and working place safety
- Studies on inhalation and health effects
- Process surveillance
- Studies on the emission of printers

特点

- Expandable to U-SMPS spectrometer
- Automatic measurement data storage
- Measurement of the particle size distribution of condensed particles for quality assurance
- Integrated pump
- Integrated computer with 7" touchscreen

技术数据

测量范围(数量浓度)	10 ⁴ particles/cm ³ (single count mode), 10 ⁴ – 10 ⁷ particles/cm ³ (nephelometric mode)	测量范围(粒径)	4 – 5,000 nm
体积流量	0.9 l/min (others on request)	Time resolution	min. 1 s
接口	TCP-IP ASCII, MODBUS, UDP, AK (on request)	User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Data logger storage	4 GB	软件	PDAnalyze
Detection efficiency (at low particle size)	D50 = 4.5 nm (others on request)	Data acquisition	Digital, 20 MHz processor, 256 raw data channels
Light source	LED	Installation conditions	+10 – +30 °C (others on request)
Accuracy	5% (single count mode), 10% (nephelometric mode)	Response time	t ₉₀ < 2.8 s, t ₉₀₋₁₀ < 2.0 s
Arbeitsflüssigkeit	1-Butanol	Dimensions	290 • 240 • 350 mm (H • W • D)

标准和证书

ISO 27891:2015