

U-RANGE 2000



The Palas U-RANGE combines two systems for continuously measuring airborne particles in a size range of 4 nm to 40 μm (depending on the configuration).

The U-SMPS is a standard system for exact measurements of nanoparticle size distributions. Aerosol particles are selected in the classifier (DEMC) according to their electrical mobility and then counted by a condensation particle counter (UF-CPC). Prof. Wiedensohler (IfT Leipzig, Germany) developed the algorithm used by Palas for the inversion of the measured data to yield the particle size distribution for the U-SMPS.

The Fidas[®] 200 is a fine dust measurement system for ambient air quality measurements for regulatory purposes. It uses the recognized measurement technology of optical light scattering of single particles and is equipped with an LED light source with stable output and a long lifetime.

优势

- Particle size distributions from 4 nm to 40 μm
- Additional determination of PM fractions (e.g. PM_{2.5}, PM₁₀)
- Continuous and fast-scanning principle of measurement
- High resolution in up to 64 size classes/decade
- Graphic display of measurement values
- Intuitive operation using 7" touchscreen and GUI
- Integrated data logger
- Supports multiple interfaces and remote access
- Low maintenance
- Reliable function
- Reduces your operating expenses

应用领域

- Aerosol research
- Environmental and climatic studies
- Inhalation experiments
- Filter test
- Interior and workplace measurements
- Distribution studies (e.g. fires, volcanoes)

技术数据

| | |
|--------------------------|--|
| 粒径范围 | 8 – 40,000 nm |
| 体积流量 | 4.8 l/min |
| Volume flow (sheath air) | 2.5 – 10 l/min |
| Size channels | Max. 120 (32/decade) |
| Time resolution | 3 min |
| 接口 | USB, Ethernet (LAN), Wi-Fi, RS-232/485 |
| User interface | Touchscreen, 800 • 480 pixel, 7" (17.78 cm) |
| Data logger storage | 4 GB |
| 软件 | PDAnalyze |
| 电源 | 115 – 230 V, 50/60 Hz |
| Working fluid | Butanol, isopropanol, water or other (UF-CPC) |
| Dimensions | Fidas [®] : 185 • 450 • 320 mm (H • B • T) (19"), UF-CPC: 330 • 380 • 240 mm (H • B • T), U-SMPS Säule: 150 • 570 mm (ø base • H, U-SMPS), U-SMPS Kontrolleinheit: 330 • 380 • 240 mm (H • B • T) |
| 重量 | Approx. 9.3 kg (Fidas [®] , U-SMPS column), approx. 12.9 kg (U-SMPS control unit), approx. 10 kg (U-SMPS UF-CPC) |

标准和证书

EN 16976:2024-09, CEN/TS 17434:2020, ISO 27891:2015, ISO 21501-1