

U-RANGE 2000



The Palas U-RANGE combines two systems for continuously measuring airborne particles in a size range of 4 nm to 40 μm (depending on the configuration).

The U-SMPS is a standard system for exact measurements of nanoparticle size distributions. Aerosol particles are selected in the classifier (DEMC) according to their electrical mobility and then counted by a condensation particle counter (UF-CPC). Prof. Wiedensohler (IfT Leipzig, Germany) developed the algorithm used by Palas for the inversion of the measured data to yield the particle size distribution for the U-SMPS.

The Fidas[®] 200 is a fine dust measurement system for ambient air quality measurements for regulatory purposes. It uses the recognized measurement technology of optical light scattering of single particles and is equipped with an LED light source with stable output and a long lifetime.

优势

- Particle size distributions from 4 nm to 40 μm
- Additional determination of PM fractions (e.g. PM_{2.5}, PM₁₀)
- Continuous and fast-scanning principle of measurement
- High resolution in up to 64 size classes/decade
- Graphic display of measurement values
- Intuitive operation using 7" touchscreen and GUI
- Integrated data logger
- Supports multiple interfaces and remote access
- Low maintenance
- Reliable function
- Reduces your operating expenses

应用领域

- Aerosol research
- Environmental and climatic studies
- Inhalation experiments
- Filter test
- Interior and workplace measurements
- Distribution studies (e.g. fires, volcanoes)

技术数据

粒径范围	8 – 40,000 nm	体积流量	4.8 l/min
Volume flow (sheath air)	2.5 – 10 l/min	Size channels	Max. 120 (32/decade)
Time resolution	3 min	接口	USB, Ethernet (LAN), Wi-Fi, RS-232/485
User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)	Data logger storage	4 GB
软件	PDAnalyze	电源	115 – 230 V, 50/60 Hz
Arbeitsflüssigkeit	Butanol, isopropanol, water or other (UF-CPC)	Dimensions	Fidas®: 185 • 450 • 320 mm (H • B • T) (19"), UF-CPC: 330 • 380 • 240 mm (H • B • T), U-SMPS Säule: 150 • 570 mm (ø base • H, U-SMPS), U-SMPS Kontrolleinheit: 330 • 380 • 240 mm (H • B • T)
重量	Approx. 9.3 kg (Fidas®, U-SMPS column), approx. 12.9 kg (U-SMPS control unit), approx. 10 kg (U-SMPS UF-CPC)		

标准和证书

EN 16976:2024-09, CEN/TS 17434:2020, ISO 27891:2015, ISO 21501-1