

# U-SMPS 1050 X/1100 X/1200 X



A soft X-ray source as a neutralizer is already integrated. The advantage instead of a radioactive neutralization (for example, with Kr-85) is that there is no need to follow requirements during transportation.

## 工作原理

## 优势

- Particle size distributions from 4 nm to 440 nm
- Continuous and fast-scanning principle of measurement
- High resolution in up to 64 size classes / decade
- Suitable for concentrations of up to  $10^8$  particles/cm<sup>3</sup>
- Universally connects to DMAs and nanoparticle counters from other manufacturers
- Graphic display of measurement values
- Intuitive operation using 7" touchscreen and GUI
- Integrated data logger
- Supports multiple interfaces and remote access
- Low maintenance

\* Please contact Palas® for further details.

## 标准和证书

ISO 15900:2010, ISO 27891:2015

## 技术数据

测量范围(数量浓度)	0 – 10 <sup>8</sup> particles/cm <sup>3</sup>
测量范围(粒径)	4 – 440 nm
Volume flow (sheath air)	2.5–20 l/min (others on request)
Size channels	Max. 256 (128/decade)
User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Data logger storage	4 GB
软件	PDAnalyze
电源	90 – 264 V, 50/60 Hz
Installation conditions	+10 – +30 °C (others on request)
Adjustment range (voltage)	1 – 10,000 V
Neutralizer	XRC 049
Data Management	Prepared for connection to the Palas Cloud MyAtmosphere ("MyAtmosphere-ready"); Internet access and separate registration required. The MyAtmosphere terms of use apply.

## 应用领域

- Filter test
- Aerosol research
- Environmental and climatic studies
- Inhalation experiments
- Interior and workplace measurements



Mehr Informationen:  
<https://www.palas.de/zh/product/usmps1050x1100x>