

# U-SMPS 2050 X/2100 X/2200 X



A soft X-ray source as a neutralizer is already integrated. The advantage instead of a radioactive neutralization (for example, with Kr-85) is that there is no need to follow requirements during transportation.

## 工作原理

## 优势

- Particle size distributions from 4 nm to 1.2  $\mu\text{m}$
- Continuous and fast-scanning principle of measurement
- High resolution in up to 128 size classes/decade
- Suitable for concentrations of up to  $10^8$  particles/ $\text{cm}^3$
- Universally connects to DMAs and nanoparticle counters from other manufacturers
- Graphic display of measurement values
- Intuitive operation using 7" touchscreen and GUI
- Integrated data logger
- Supports multiple interfaces and remote access
- Low maintenance

\* Please contact Palas® for further details.

## 标准和证书

ISO 15900:2010, ISO 27891:2015, CEN/TS 17434:2020

## 技术数据

测量范围(数量浓度)	0 – 10 <sup>8</sup> particles/cm <sup>3</sup>
测量范围(粒径)	4 – 1,200 nm
体积流量	0.5 – 3 l/min
Volume flow (sheath air)	2.5–20 l/min (others on request)
Size channels	Max. 256 (128/decade)
接口	USB, Ethernet (LAN), AUX, RS-232 (CPC only)
User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Data logger storage	4 GB
软件	PDAnalyze
电源	90 – 264 V, 50/60 Hz
Installation conditions	+10 – +30 °C (others on request)
Adjustment range (voltage)	1 – 10,000 V(UP and DOWN scan possible)
Neutralizer	XRC 049
Data Management	Prepared for connection to the Palas Cloud MyAtmosphere ("MyAtmosphere-ready"); Internet access and separate registration required. The MyAtmosphere terms of use apply.

## 应用领域

- Filter test
- Aerosol research
- Environmental and climatic studies
- Inhalation experiments
- Interior and workplace measurements



Mehr Informationen:

[https://www.palas.de/zh/product/usmps2050x<sub>2</sub>100x](https://www.palas.de/zh/product/usmps2050x2100x)